

120L Refrigerated Display

OPT-RDC-1G-120L

Specifications



Capacity	120L
Display Area	0.97 m ²
Energy Consumption	3.09 kWh per 24 hours
Product Size W x O x H (mm)	660 x 650 x 1920
Packaging Size W x O x H (mm)	740 x 700 x 2075
Inside Cabinet Size	590 x 505 x 1665 Stair DxH: 185 x 172
Cabinet Temperature (°C)	0-10°C
Cooling System	Fan cooling
Fan Motor	29W
Defrost	Manual
Compressor	FTA 66L
Refrigerant (CFC-free)	R290/85G
Evaporator	Copper tube evaporator 6 x 6 x 300
Condenser	Ø 4.76 galvanised pipe
Door Frame	PVC
Glass Type	Double-glazed 3mm float glass
Adjustable Shelves	4 pcs
Wheels	4 pcs
Internal Light	LED/1.4M
Outer Cabinet	Coated Steel 0.45mm Spraying powder thickness: 0.02mm
Inside Cabinet	Coated Steel 0.3mm Spraying powder thickness: 0.02mm
Net Weight (kg)	85
Gross Weight (kg)	105

Construction

- Coated steel 0.40mm thick body with spray powder coated finish
- 100% CFC-free Polyurethane foam interior cabinet liner
- 4x adjustable footing on castor wheels
- PVC Door Frame
- Double Glazed 3mm float glass door
- Galvanised Ø 4.76 pipe condenser
- Expanded Aluminium Plate Evaporator
- R600a Iso-Butane Refrigerant with low GWP

Features

- Static Cooling
- Thermostatic Temperature Control
- Adjustable Shelves
- LED Lighting
- Robust Design
- 0-10°C Temperature Range
- Large Display Area
- Low Total Energy Consumption (kWH/24Hrs) rating